



MOTORISED LENS 4MP IR SMART CAMERA

MOTORISED ZOOM ♦ AUTO-FOCUS ♦ SMART ALGORITHM ♦ IP67

RESOLUTION
4MP

IR RANGE
30M

LENS
2.8-12MM

SMART

WEATHER PROOF
IP67



IP

FEATURES

- 4MP (2592x1520) Resolution
- 2.8-12mm motorised lens
- Intelligent identification
- Statistical analysis
- Embedded smart algorithm
- Ultra 265/H.265/H.264/MJPEG
- 9:16 corridor mode
- Motorised zoom with auto-focus
- Smart IR, up to 30m
- IR-Cut filter
- IP67 Waterproof housing
- Two-way audio
- Triple streams
- Audio detection
- ONVIF conformance
- 2D/3D Digital noise reduction
- IR Anti-reflection window
- Micro SD, up to 128GB supported


ACCESSORIES (SOLD SEPERATELY)

M1P-APM01



POLE MOUNT

M1P-DB3C1



7" DEEP BASE
JUNCTION BOX

M1P-AWJ01



WATERPROOF JOINT

AVAILABLE NOW

CONTACT YOUR DISTRIBUTOR FOR MORE DETAILS.

	MODEL	M1P-C3C40M
CAMERA	Image Sensor	1/3" 4MP Progressive Scan CMOS Sensor
	Effective Pixels	2592x1520
	Shutter	Auto/Manual, 1/6~1/100000 s
	S/N Ratio	≥52dB
LENS	Min. Illumination	Colour: 0.02 Lux (F1.4, AGC ON) 0 Lux with IR
	Focus Length	2.8~12mm
	Angle of View	91.0°~27.0°
	Focus Control	Auto
FEATURES	Lens Type	Motorised
	IR Range	Up to 30m (98ft)
	Day/Night	IR-cut filter with auto switch (ICR)
	Auto White Balance	Auto/manual
	Defog	Digital Defog
	Gain Control	Auto/manual
	Noise Reduction	2D/3D DNR
	HLC / BLC	Supported
	9:16 Corridor Mode	Supported
	On-Screen Display	Up to 8 OSDs
	Privacy Mask	Up to 8 areas
	Region of Interest	Up to 8 areas
	Motion Detection	Up to 4 areas
Edge Storage	Micro SD, up to 128 GB	
SMART	Behavior Detection	Intrusion, cross line, motion detection
	Exception Detection	Audio detection
	Intelligent Identification	Face detection, Defocus, Scene Change
	Statistical Analysis	People counting
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication	
NETWORK	Video Compression	Ultra 265,H.265, H.264, MJPEG
	H.264 code profile	Baseline profile, Main Profile, High Profile
	Frame Rate	Main Stream: 4MP (2592x1520): Max. 20 fps, 4MP (2560x1440): Max. 25 fps, 3MP (2048x1520): Max. 30 fps Sub Stream: 2MP (1920x1080): Max. 30 fps Third Stream: D1(720x576) : Max. 30fps
	Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP
Compatible Integration	ONVIF(Profile S, Profile G), API	
Network Storage	ANR	
INTERFACE	Network Interface	10M/100M Base-TX Ethernet
	Audio I/O	Two-way, Audio Cable
	Alarm I/O	1 / 1
GENERAL	Ingress Protection	IP67 Waterproof
	Operation Temp.	-35°C ~ +60°C, RH95% Max
	Power	DC12V±25%, PoE (IEEE802.3 af). Consumption: Max 5.5W
	Dimensions	253.4 x86 x71.7 mm
Weight	0.58 kg	